

## FOAM CHARIOT I & II QUOTE MENU

Check  
One

10 K GVW DUAL TOTE 275 OR 330 GAL  
 5 K GVW SINGLE TOTE 275 OR 330 GAL  
 2 OPEN TOP HOSE STORAGE CABINETS  
 2 TRIPLE HINGED STORAGE COMPARTMENTS  
 NFPA LIGHTS AND STRIPES

RADIO CONTROLLED MONITOR  
 MANUAL CONTROLLED MONITOR  
 MONITOR UP TO 1250 GPM  
 MONITOR UP TO 2000 GPM  
 VALVE UNDER MONITOR - RADIO CONTROLLED  
 NF GLADIATOR TRI-FLOW 500-750 -1000 GPM  
 SELF INDUCTING MASTER 500 GPM  
 SELF INDUCTING MASTER 750 GPM  
 SPECIFY OTHER \_\_\_\_\_  
 95 OR 125 GPM FOAM HANDLINE KIT 1 OR 2  
 BLITZFIRE (OSCILLATING) MONITOR KIT  
 FOAM TRANSFER PUMP KIT (23 GPM 120V)

INTAKE VALVE RIGHT  
 INTAKE VALVE LEFT  
 PLAIN STORZ & CAP RIGHT  
 PLAIN STORZ & CAP LEFT  
 STORS WITH WYE RIGHT  
 STORS WITH WYE LEFT  
 RISER RELIEF VALVE IF NO INTAKE VALVES



Foam Chariot I



DESIGN PATENTS PENDING



Foam Chariot II

